

## QUESTIONS & ANSWERS

### IN OPEN INTERNATIONAL PROCEDURE FOR

**Procurement of furniture, kitchen equipment and laundry equipment for the equipping of dormitories within the project “Education for Social Inclusion” CEB F/P 1746 (2011)**

**ICB No: RS/CEB-F / P 1746 (2011) -G-ICB-01/2021/METD**

**Lot No. 1:** Procurement of furniture

**Lot No. 2:** Procurement of kitchen equipment

**Lot No. 3:** Procurement of laundry equipment

Ref. Receipt	Questions	Answers
<b>Q1</b> <b>Request</b> <b>attach to</b> <b>email</b> <b>11.02.2022</b>	<b>Lot No. 2</b>  Student dormitory of the Agricultural School with dormitory "Sonja Marinkovic" in Pozarevac, <ul style="list-style-type: none"> <li>• Meat warehouse - Positions 2, 3 and 7 - Shelving</li> <li>• Bakery - Position 2 - Shelving</li> </ul> The description reads: "... Shelves with partitions at 500mm .. “ Is it thought that the distance between the shelves is 500mm or something else? If you meant space, then match the number of shelves with the height of the rack, if you meant the partitions on the shelves themselves, explain what they should look like and how they should be placed.	Distance of 500mm refers to the distance between horizontal shelves (racks). The total height of the element includes the adjustable legs. The number of shelves (racks) should be the maximum possible within these dimensions, but provided that the minimum distance between them is not less than 500 mm.
<b>Q2</b> <b>Request</b> <b>attach to</b> <b>email</b> <b>11.02.2022</b>	<b>Lot No. 2</b>  Student dormitory of the Agricultural School with dormitory PK "Belgrade", - Thermal block - kitchen - Position 34 and 35 - hood Since it is stated that both positions are provided by the project of mechanical installations, we assume that it is not necessary to make an offer for them.	The note given next to the position of the hood, that the hoods are provided by the project of mechanical installations, is supplemented by the following clarification: It is necessary for the Bidder to submit bids for hoods according to the given description. The bidder should keep in mind that the project of mechanical installations envisages that: <ul style="list-style-type: none"> <li>• The hood under position 34 (ie the larger hood above the thermal block) must be an ECO hood and a 700x300mm duct with a capacity of</li> </ul>

		<p>5000m<sup>3</sup>/h for air extraction and a 700x300mm duct with a capacity 3500m<sup>3</sup>/h for air compensation.</p> <ul style="list-style-type: none"> <li>•The hood under position 35 (ie smaller hood) is a classic professional kitchen hood for extracting air and a duct measuring 200x200mm with a capacity of 800m<sup>3</sup>/h is made next to it.</li> </ul> <p>All inlet and outlet ducts are already equipped with motors according to the project. The hood itself must be made and installed in the given position with the prepared connection to the duct system. Only the connection to the duct system is performed by the Contractor of the duct system, while the connection to the electrical installations required for the hood itself is done by the hood supplier (via an electrical outlet prepared for that by the electrical contractor).</p>
<p><b>Q3</b> <b>Request</b> <b>attach to</b> <b>email</b> <b>14.02.2022</b></p>	<p><b>Lot No. 2</b></p> <p>Student dormitory of the Agricultural School with the dormitory "Sonja Marinkovic" in Pozarevac, Meat Warehouse - Position 1 - Track. We kindly ask for clarification along with the drawing of the track with dimensions. From the description of the position given in this way, it is not clear what the track should look like and what its dimensions are. It is not possible to make an offer without the requested information.</p>	<p>The track is 1200 mm wide, made of stainless steel, pipe fi 60, hanging on the wall with galvanized supports, load capacity 200 kg/m.</p> <p>In the graphic attachments, it is shown within the minus cooling chamber for meat, but it will be placed on the right wall of the plus chamber. Although it is called "track", it is not a classic ceiling track that is used in slaughterhouses, but a simple solution for hanging meat (a couple of halves) on the mentioned side wall and it consists of a bar 1200mm wide remotely attached to the wall away from its 400mm.</p>

Procurement Commission